



Diesel Generator Set MP-50

Genset Specification

kVA [Prime]	50
kW [Prime]	40
Motor Marke	Mahindra & Mahindra Ltd.
Motor Model	4575 GMA C2
Alternator	Stamford or Leroy Somer
Phase	3-Phase
Voltage [V]	400, 3-Phase
Frequency [Hz]	50
Engine Speed [RPM]	1500
Rated Current [A]	70, 3-Phase
Fuel Tank Capacity [l]	177
Noise Level at 1 m DB(A)	75
Conformance to Standards	ISO 8528
Dimensions (LxWxH) [mm]	2410 x 1050 x 1600*
Weight, net [kg]	1260

*high without silencer and load hook

Engine

Model	4575 GMA C2
Engine Power @ 100% Load [HP]	65.4
Cylinder	4
Displacement in cc	3192
Governing Class	Electrical
Starting System [V]	12, Electrical
Cooling System	Water cooled with Radiator
Fuel Consumption @ 100% Load [l/h]	12.4
Fuel Consumption @ 75% Load [l/h]	9.5
Emission class	Stage 3A
Fuel	Diesel

Alternator

Model	Stamford or Leroy Somer
Type	Brushless
Power Factor [cos φ]	0.8
Insulation Class	H
Ingress Protection	IP 23



Control

Make	Deep Sea
Type	Controller 4521
Control	Manual / Automatic - ATS included
Display	LCD
Protection	Engine-High Water Temperature, Low Lube oil pressure, Low Fuel Level Electrical – Generator Under / Over Voltage, Generator Under / Over Frequency, Generator Over Current, Generator kW Overload



K&W Drive Systems SRL

Str. Brazilor, nr.74, Brasov, Romania, 500313
 Mobil: +40728212664
 Email: kwds@kwds.ro
 www.stromerzeuger-blackout.com

